Technical information

[/spotguard pro]



Spotguard PRO is a compact battery operated tracking device optimized for low power consumption. The device is waterproof (IP67) and has an internal battery for flexible installation. An internal RF beacon can be activated for recovery purposes. An internal G-sensor detects any movement between report intervals.

facts

- > Positioning with GPS and GSM triangulation
- > Web interface
- > Records temperature, movement and battery
- > Water and dust resistent (IP67)
- No external connections
- > Power: internal battery, 38Ah (Lithium)

[benefits]

- > Autonomous positioning system
- > Adjustable settings, frequent measurements
- > Programmable alerts and alarms based on defined values
- > Documentation and history

[key functions]

- > Activity based positioning
- > Short reporting intervals on the move
- > Sleep mode with 12h reporting when inactive
- > Movement indication
- > Extreme battery lifetime up to 25.000 reports (at 25 °C and good cellular coverage)

[certificates and approvals]

- > RED 3.1.a, 3.1.b, 3.2
- > 2011/65/EC (ROHS2),EC 1907/2006 (REACH), 2012/19/EU (WEEE),CE
- > No water intrusion

[temperature readings]

- > Internal temperature is indicated in every position report
- > Full history and drill-down functionality in the web based user interface.

[physics]

- > Water resistant; IP67.
- > Dimmensions: 160x90x40mm
- > Weight: 450g

[User interface] > Web portal and App

Power Consumption 1S2P Lithium D-cell (38.000 mAh) **Battery** 12h:30m:8h movement 24h 2,2 mAh 1.5 mAh Power consumption per. report 2 Average # reports per. day 18 Sleep mode consumption per. day 0.4 mAh 0.4 mAh Average consumption per. day 4,4 mAh 24,8 mAh Estimated battery lifetime 10+ years 3,5 years

Reporting every 12h and every 30 min at movement in 8 hours per day (at 25 $^{\circ}$ C and good cellular coverage).

